



**Product Introduction:**

1. Adhesive Lined Heat Shrinkable Tube for Automotive Oil Pipe Protection is specially designed to protect the automotive oil pipe from librations and frictions during operation, and greatly improve the safety of automotives;
2. Shrink temperature: 120 °C;
3. Operating temperature: -45 °C ~ 105 °C;
4. RoHS compliant.

**Standard Color:** Black (Other color available upon request.)

**Technical Data:**

Property	Test Method	Stantard
Tensile Strength	ASTM D2671	≥ 12MPa
Elongation	ASTM D2671	≥ 300%
Longitudinal Shrinkage	UL224	± 10%
Operating Temperature	IEC216	-55°C ~ +105°C
Flexibility under low Temperature	ASTM D746	No Cracking at -35 oC;

**Specification:**

Size (mm)	As Supplied	After Recovery (mm)			Application Range		Standard Packing (m/spool)
	I. D.(mm)	Min. W.T.(mm)	Thickness of Adhesive Layer(mm)	I.D.(mm)	inch	mm	
Φ5.0	≥5.5	1.0	0.3±0.1	≤3.3	1/8	3.5	200
Φ6.0	≥6.5	1.0	0.3±0.1	≤4.6	3/16	4.76	200
Φ8.0	≥8.5	1.0	0.3±0.1	≤6.0	1/4	6.35	100
Φ11.0	≥11.5	1.1	0.3±0.1	≤7.0	5/16	8.0	100
Φ15.0	≥15.0	1.2	0.3±0.1	≤9.5	3/8	10.0	100