



Product Introduction:

Silicone Rubber Braided Tube is Braided glass fibrin and silicone colophony .General insulating protection for various household appliances, light fitting ,machines, electronic instruments etc.

Characteristics:

- 1.Operating temperature ranges : -60°C~200°C
- 2.With good flexibility and arc-resistant, corona-resistant;

Standard color :white (Other color available upon request.)

Technical data:

Property	Test method	Standard
Dielectric strength (kv/mm)	GB/T 1408	≥ 18
Volume resistance	GB/T 1410	≥ 1 × 10 ¹⁴
Tensile strength,Mpa	GB/T 1040	≥ 4MPa
Elongation,%	GB/T 1040	≥ 210
Flammability	GB/T 2408	FV-1

Specification:

Size (mm)	Standard size (mm)			Standard package (m/spool)
	I.D.	Min.W.T.	Average W.T.	
1.0	1.0±0.15	0.60	0.80	200
2.0	2.0±0.15	0.60	0.80	200
3.0	3.0±0.15	0.80	1.00	100
4.0	4.0±0.15	0.80	1.00	100
5.0	5.0±0.20	0.80	1.00	100
6.0	6.0±0.20	1.00	1.20	100
7.0	7.0±0.20	1.00	1.20	50
8.0	8.0±0.25	1.00	1.20	50
9.0	9.0±0.25	1.20	1.50	50
10.0	10.0±0.25	1.20	1.50	50