

## Product info

### product :

model : T1/11-B3

### Specifications :

Rating : AC125/250V, 5A/7.5A/10A/15A

Open Temp : 0°C~250°C (According to Request of Customers)

Tolerance of Open Temp :  $\pm 1.5^{\circ}\text{C}$  ;  $\pm 2^{\circ}\text{C}$  ;  $\pm 3^{\circ}\text{C}$  ;  $\pm 5^{\circ}\text{C}$  ;  $\pm 10^{\circ}\text{C}$

Difference between Open and Close Temp : 5~200°C

Tolerance of Close Temp :  $\pm 3^{\circ}\text{C}$  ;  $\pm 5^{\circ}\text{C}$  ;  $\pm 10^{\circ}\text{C}$

Dielectric Strength : AC1,800V for 1 minute;

Insulation Resistance :  $\geq 5\text{M}\Omega$  (at DC 500V)

Contact Resistance :  $\leq 50\text{m}\Omega$

Heat-Resistant Spec : PF 180°C, UP/PPS 220°C, EC 250°C  
(24Hours)

Lifetime Resisitive : 100,000 cycles

### Application :

Water heater & relative appliance

Electric refrigerator & relative appliance

Coffee maker

Microwave oven

Sterilized cupboard

High power heater.

